


Interfacing LCD Modules to the STC12LE5A60S2 MCU

The Serial (4line SPI)Reference Example



ERM12864-9

注:PIN1-- PIN4为外部字符芯片的引脚,如果不使用字库芯片,这些脚需要悬空.  
字库内容可选(更换字库芯片)

- 16\*16 GB2321(6763)
- 8\*8 12\*12 16\*16 24\*24 173国外文
- 16\*16 日文汉字(6763)

Note: PIN 1 to PIN4 for external font chip pins, if do not use font chip, these pins need to keep open.  
Font optional (replace font chip)

16 \* 16 GB2321 (6763)

- Unicode (173 countries' language): 5x7 ~ 24x24  
(Latin, Greek, Cyrillic, Arabic, Hebrew, Thai)
- ISO8859 (14 sets): 5x7, 8x16
- ASCII (11 sets): 5x7 ~ 24x24
- LCM Character Set (8 sets): 5x7, 5x10
- 16 \* 16 Japanese characters(6763)

Title EASTRISING TECHNOLOGY CO.,LTD.

REV.	DESCRIPTION OF MODIFY	MODIFY BY	DATE	Size	Number	Revision
A0	1' ST DESIGN	JIM	28-Jun-2023	A	ERM12864-9	A0
A1				Date:	28-Jun-2023	Sheet of 1
				File		Drawn By Jim