

ER-DBO0.54-1

MCU 8051 Development Board & Kit User Guide



EastRising Technology Co., Limited

Attention:

- A. Some specifications of IC are not listed in this datasheet. Please refer to the IC datasheet for more details.
- B. The related documents for interfacing, demo code, ic datasheet are all available, please download from our web.

REV	DESCRIPTION	RELEASE DATE
1.0	Preliminary Release	May-31-2023

CONTENTS

1. ORDERING INFORMATION	03
2. QUICK START	04
3. BUTTONS DEFINITIONS	05
4. SPECIFICATION	06
5. OUTLINE DRAWING	07
6. HOW TO MAKE A CUSTOM DEMONSTRATION	08
7. METHODS FOR USING IN SYSTEM PROGRAMMING	08
8. CARE AND HANDLING PRECAUTIONS	14

1. ORDERING INFORMATION

1.1 Order Number


Part Number(Order Number)	Description
ER-DBO0.54-1	8051 Microcontroller Development Board & Kit

1.2 What's included in the package

No	Standard Accessory Name	Quantity
1	MCU Board	1
2	Adaptor Board	1
3	Power Adaptor (12V/2)	1
4	USB Cable	1

2. QUICK START

2-1 Simply plug the power adaptor into an AC outlet and plug FFC(Cable) of lcd display into the ZIF connector of adaptor board as the below image shows.




2-2 Press the power button to run the demonstration program.

3. BUTTONS DEFINITIONS

Button Name	Description
*Stop/Next Button	Stop or Next the Image Slideshows
Reset Button	Restart to Initialized State
Power Button	Press On or Press Off

*For color display, this button is used to next the image slideshows.

For mono display, this button is used to stop the image slideshows.



4. SPECIFICATION


4.1 Mechanical Specification

ITEM	STANDARD VALUE	UNIT
MCU Board Outline Dimension	151.00×77.00	mm
Adaptor Board Outline Dimension	90.00×95.00	mm
Gross Weight for Whole Demo Kit	0.60	kg

4.2 Electrical Specification

ITEM	STANDARD VALUE	UNIT
Microcontroller	STC12LE5A60S2	--
Interface	I2C	--
Power Supply Voltage	12V	V

5. OUTLINE DRAWING



BuyDisplay.com
EastRising Technology Co., Ltd.

TEL: 86-755-33503871 Email: sales@buydisplay.com

APPROVALS: DATE: GENERAL TOL: UNITS: MM

APP: Drawing Name: 8051 Demo Board SCALE: N.T.S.

CHK: DWN: JIM 150116 DO NOT SCALE THIS DRAWING. PROJECTION: SHEET: 1

6. HOW TO MAKE A CUSTOM DEMONSTRATION

By using the software of LCD Font Maker or Image2LCD and ISP(In System Programming) to customize the demonstration that includes your own bitmap images, personalized fonts, symbols, icons and burn sketches. The large capacity of the MicroSD card allows you to store more fonts or images. We also prepare the demo code, interfacing document (download from each product page) and schematic MCU datasheet (download from each 8051 microcontroller development board page) for your further study.

LCD Font Maker: <http://www.buydisplay.com/download/software/LCDFontMaker.zip>

Image2LCD: <http://www.buydisplay.com/download/software/Image2Lcd.zip>


7. METHODS FOR USING IN SYSTEM PROGRAMMING

7-1 Hardware Preparation

7-1-1 Please power off the development board,


7-1-2 No power supply is connecting with 8051 development board,

7-7-3 The jumpers on JP8 is on ISP position as below image shows



7-2 Install the USB to RS232 Driver

<http://www.buydisplay.com/download/software/USB-TO-RS232-DRIVER.rar>




7-3 Connecting the 8051 development board to computer by USB Cable and you should find the new port USB-SERIAL CH340 in Computer-System Properties-Device Manager as below image shows and remember the COM number that would be used in Step7-4.




7-4 Install STC 8051 Microcontroller ISP(In System Programming)Software

<http://www.buydisplay.com/download/software/STC-ISP-V4.86-NOT-SETUP-ENGLISH.zip>


7-5 Open ISP and Select COM Port that should be the same with the step 7-2 you see from Device Manager.



7-6 Select MCU part number that should be the same with your purchased one.
(Refer to 4.2 Electrical Specification)




7-7 Open target ".hex" file by clicking open code file




7-8 Programming

7-8-1 Click Download/Program




The screenshot shows the STC-ISP (V6.82H) software interface. The 'Download/Program' button is highlighted with a red box. The interface includes various settings for MCU Type (STC12LE5A60S2), COM Port (USB-SERIAL CH340), and baud rates. A table of MCU models is visible, and the 'Download/Program' button is located at the bottom left of the main settings area.

7-8-2 Then you will see "Checking target MCU...."



The screenshot shows the STC-ISP software interface during the programming process. The 'Checking target MCU....' status message is highlighted with a red box. The interface displays a hex dump of memory addresses from 00000h to 00100h. The 'Download/Program' button is still visible at the bottom left.

7-8-3 Power on the development board by pressing the white power button



7-8-4 Now you could see the process of programming

A screenshot of a programming software interface. The top section shows a hex dump of memory addresses and their corresponding values. Below this is a control panel with buttons for 'Code-Size', 'Checksum', 'Fill-Buffer', 'Clear-Buffer', and 'Save-Buffer'. The main display area shows the following text:


```
. MCU type: STC12LE5A60S2  
F/W version: 6.2I  
  
Re-handshaking ... Successful [0.609"]  
Current Baudrate: 57600  
Erasing MCU flash ... OK ! [2.562"]  
MCU ID : 000300B00C325F  
Programming user code ...
```

At the bottom, there are buttons for 'Release Project', 'Release Help', 'Get HDD-SN', a checked 'Beep' checkbox, 'PassTimes' set to 2, and a 'Reset' button.

7-8-5 Programming Finished



8 Please move the jumpers on JP8 from ISP to N_ISP as below image shows.



8. CARE AND HANDLING PRECAUTIONS

The kit is sold with a module mounted on it. If you attempt to modify the board to work with other modules, the warranty is void. For optimum operation of the module and demonstration board and to prolong their life, please follow the precautions below.

8.1 ESD (Electro-Static Discharge)

The circuitry is industry standard CMOS logic and susceptible to ESD damage. Please use industry standard antistatic precautions as you would for any other PCB such as expansion cards or motherboards.

8.2 Avoid Shock, Impact, Torque and Tension

- ◇ Do not expose the module to strong mechanical shock, impact, torque, and tension.
- ◇ Do not drop, toss, bend, or twist the module.
- ◇ Do not place weight or pressure on the module.

8.3 LCD&OLED Display Glass

- ◇ The exposed surface of the LCD "glass" is actually a polarizer laminated on top of the glass. To protect the soft plastic polarizer from damage, the module ships with a protective film over the polarizer. Please peel off the protective film slowly. Peeling off the protective film abruptly may generate static electricity.
- ◇ The polarizer is made out of soft plastic and is easily scratched or damaged. When handling the module, avoid touching the polarizer. Finger oils are difficult to remove.
- ◇ If the LCD panel breaks, be careful not to get the liquid crystal fluid in your mouth or eyes. If the liquid crystal fluid touches your skin, clothes, or work surface, wash it off immediately using soap and plenty of water.
- ◇ Be very careful when you clean the polarizer. Do not clean the polarizer with liquids. Do not wipe the polarizer with any type of cloth or swab (for example, Q-tips). Use the removable protective film to remove smudges (for example, fingerprints) and any foreign matter. If you no longer have the protective film, use standard transparent office tape. If the polarizer is dusty, you may carefully blow it off with clean, dry, oil-free compressed air.

8.4 Operation

- ◇ Use only the included AC adapter to power the board.
- ◇ Observe the operating temperature limitations: from -20°C minimum to +70°C maximum with minimal fluctuations. Operation outside of these limits may shorten the life and/or harm the display.
 - At lower temperatures of this range, response time is delayed.
 - At higher temperatures of this range, display becomes dark. (You may need to adjust the contrast.)
- ◇ Operate away from dust, moisture, and direct sunlight.

8.5 Storage and Recycling

- ◇ Store in an ESD-approved container away from dust, moisture, and direct sunlight.
- ◇ Observe the storage temperature limitations: from -30°C minimum to +80°C maximum with minimal fluctuations. Rapid temperature changes can cause moisture to form, resulting in permanent damage.
- ◇ Do not allow weight to be placed on the modules while they are in storage.
- ◇ Please recycle your outdated displays at an approved facility.

文件名: ER-DBO0
目录: \\Server-1\e\部门文件夹\3-技术部\工程文件\工程文件
_8051\Datasheet\OLED
模板: C:\Users\Administrator\AppData\Roaming\Microsoft\Templates
 \Normal.dotm
标题: ERC12864-1_Series_Manual
主题: ERC12864-1_Series_Manual
作者: EastRising
关键词: lcd display,lcd module,128x64 lcd display,128x64 lcd
 module,128x64 cog,cog,graphic module,128x64,12864,lcm
备注:
创建日期: 2015-12-08 15:03:00
修订号: 36
上次保存日期: 2024-06-27 13:56:00
上次保存者: Administrator
编辑时间总计: 242 分钟
上次打印时间: 2024-06-27 15:01:00
打印最终结果
 页数: 15
 字数: 1,419 (约)
 字符数: 8,092 (约)