




- Notes:
- Type: Film to Glass
  - Operating Voltage:  $\leq 10V$
  - operation Temperature:  $-10^{\circ}C \sim 60^{\circ}C$   
Storage Temperature:  $-20^{\circ}C \sim 70^{\circ}C$
  - Life Time:  $\geq 1,000,000$  times
  - Connect Material: FPC
  - Response Time:  $\leq 10ms$
  - Linearity:  $\leq 1.5\%$
  - Transmittance:  $\geq 80\%$
  - Surface Hardness  $\geq 3H$  (Pencil)
  - operation force:  $20g \sim 80g$
  - Resistance:  
(Clear hard ITO Film)  $x: 150\Omega \sim 500\Omega$   
(Stand ard ITO Glass)  $y: 350\Omega \sim 850\Omega$
  - Unspecified Tolerance:  $\pm 0.20$



NO.	SYMBOL
1	YU
2	XL
3	YD
4	XR



深圳旭日东方科技有限公司

**EASTRISING TECHNOLOGY CO.,LTD**

TEL:86-755-33503874

33503873 33503871

FAX:86-755-33507642-801

APPROVALS	DATE	Part Number :	GENERAL TOL.	UNITS
APP		ER-TP032-3	SCALE:	MM
CHK			N.T.S.	
JIM	160606	DO NOT SCALE THIS DRAWING.	SHEET:	1