


Item	Content	Date	Checked By
1	NEW DRAWING	May-17-2019	Mr.Jim

Top View


Side View

Bottom View

Note:
 1.Structure: film+glass+FPC
 Film:Bright screen (0.188mm)
 Glass:(1.1mm)
 Tail:FPC (pitch=1.0mm)
 2.Operating voltage: 3-7V
 3.Voltage: DCSV 1mA
 4. Insulation resistance: ≥20MΩ(25V DC)
 5.Linearly: ±1.5%
 6.Transmittance: ≥75%
 7.Operation force: 50-120g
 8.Life time: ≥1,000,000
 9.Operating temp: -10℃~+60℃, ≤90%RH
 10.Storage temp: -20℃~+70℃, ≤90%RH
 11. X:350-900Ω;Y:150-500Ω
 12.Tolerance±0.20
 13.VA:Visual Area
 14.AA:Active Area



Pin NO.	Assignment
1	YU
2	XL
3	YD
4	XR


旭日东方科技有限公司
EASTRISING TECHNOLOGY CO.,LTD
 Web: www.buydisplay.com Email: sales@buydisplay.com

APPROVALS	DATE	MODEL NUMBER :	GENERAL TOL.	UNITS
APP		ER-TP080-2	N.T.S.	MM
CHK				
DWN	JIM	May-17-19	DO NOT SCALE THIS DRAWING.	PROJECTION
			SCALE:	SHEET: 1